



BW---Compact weighing indicator

Features

- ◆Function keys: Unit, M+, Net/Gross, MR/MC, Zero/Tare/On, Off
- ◆Weighing, Simple counting, Checking Weight HI-OK-LO Function, Hold(animal) function
- ◆Power On Zero-Tracking, Auto-Calibration, Auto-Power Off mode, Digital Noise Filter, Full Tare, Accumulation Memory, Programmable Capacity and Division, Low Battery Indicator and Charging Status Indicator

Specifications

- ◆Accuracy: III
- ◆Display: 23mm LCD display with LED backlit
- ◆Rechargeable battery 6V/1.3Ah for 40 hours continuous use
- ◆Power Supply: Input AC 100V-240V, Output 9V/500mA
- ◆Operating Environment: -10°C to 40°C (14°F to 104°F)
- ◆Product size: 190 mm x108 mm x55 mm
- ◆Load cell:Up to 4x350ohm minimum resistance
- ◆Display/Internal Resolution:30,000/600,000

Option

- ◆RS232 output , Relay output and Bluetooth



Carbon steel platform			Stainless steel platform		
Stainless or carbon steel platter			Stainless steel platter		
Model	Size(mm)	Cap.(kg)	Model	Size(mm)	Cap.(kg)
BWC2828	280*280	3-30	BWS2828	280*280	3-30
BWC3030	300*300	15-150	BWS3030	300*300	15-150
BWC3040	300*400	30-150	BWS3040	300*400	30-150
BWC4040	400*500	30-150	BWS4040	400*400	30-150
BWC4050	420*520	30-300	BWS4050	400*500	30-300
BWC4252	420*520	60-300	BWS4252	420*520	60-300
BWC5060	500*600	60-600	BWS5060	500*600	60-600

Aluminum Die-Cast platform		
Stainless steel platter		
Model	Size(mm)	Cap.(kg)
BWA3040	300*400	30-150
BWA4252	420*520	60-300